

MCW "PROFESSIONAL" SERIES CRANE SCALES



Crane scales MCW and MCWR2

WEIGHTS OF THE CRANE SCALES

Models	Weight in kg	
	without packing	including packing
MCW...R2	18 kg	20 kg
MCW	14 kg	16 kg



AVAILABLE FUNCTIONS FROM REMOTE CONTROL

- **Infrared 19-key remote control** (standard), operating up to 8m:
zero; tare / manual tare; enable / disable function; print; switch-off.
- **Radiofrequency 6-key remote control** (optional) operating up to 50m:
zero; tare; enable / disable function; print; switch-off.

Reliable and easy to use AISI 304 stainless steel crane scales suitable for indoor and outdoor use, for industrial weighing applications. Reduced lifting distance of the crane. IP67 protection from dust and rain. Available also CE-M APPROVED. Fitted with test certificate obtained with sample weights.

MAIN FEATURES

- Large backlit 25mm LCD display easily visible in all lighting conditions and also with low temperatures.
- Fitted with standard approved upper galvanized shackle and standard approved bottom hook.
GR3 and GOC1 for MCWR2 (150/300/600/1500)
GR6 and GOC3200 for MCW3000
GR6 and GOA8 for MCWT6
- Reduced distance between the upper shackle and bottom hook.
- Precision: +/- 0.05% F.S.
- Waterproof keyboard with 5 keys: ZERO, AUTOMATIC TARE, MODE, PRINT, and ON/OFF.
- MODE-key configurable as:
PEAK (maximum value read), HOLD (blocking the weight viewed), Weighs accumulation, lb/kg/N conversion.
See the user manual for the list of the functions.
- IP67 stainless steel case ("R2" versions).
- Fitted with remote control for up to a 8 m distance. The remote control may be configured by the customer as automatic tare only, or as a remote keypad.
- Rechargeable sealed battery with a 40-hour life battery. On request, it is available a second battery for a 24/7 use.
- Equipped with 230Vac 50 Hz battery charger.
- Operating temperature: -10 / +40 °C.
- Programmable digital filter and auto switch-off.

OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Integrated thermal printer (code TPRPR2 only for the "R2").
- WI-FI interface.
- RF weight transmission to remote indicator up to over 70m indoors, 150m outdoors, adequate environmental and installation conditions.
- 433MHz radiofrequency remote control (compatible with remote indicator).
- DOT red LED display of 40mm.
- Second battery for a 24/7 use (code MCWKBK for "R2" models; code MCWBK for MCW3000, MCW3000M, MCWT6, MCWT6M models).
- ACCREDIA calibration certificate according to OIML/ASTM standards.
- Remote weight indicator (see DFW., 3590., TRS., DGT60.. Series' indicators) with printer connected through radio frequency.