

TPWLKI SERIES STAINLESS STEEL PALLET TRUCK SCALE



Stainless steel pallet truck scales with built-in multirange electronic weighing, easy to use. Weight detection with four IP68 stainless steel load cells. Sturdy structure suitable for harsh work conditions. Available also CE-M APPROVED.

MAIN FEATURES

- Maximum lifting capacity: 2000 kg.
- Accuracy: $\pm 0.1\%$ of the maximum capacity in the versions for internal use.
- Accuracy: $\pm 0.05\%$ of the maximum capacity in the "M" approved versions.
- Fork dimensions 1180 x 550 x 80 mm. Weighs about 135 kg.
- **Bearing structure in extra thick STAINLESS steel.**
- **Lifting pump in STAINLESS steel.**
- Steering wheels and double loading rollers in nylon.
- Closed forks, for a higher protection of the double loading wheels.
- 4 IP68 stainless steel shear beam load cells.
- IP65 stainless steel weight indicator, easy to clean and resistant to harsh and corrosive environments; large 25mm backlit LCD display, clearly visible also in poor lighting conditions.
- Calibration and Set-Up from keyboard or from PC.
- Power supply through built-in rechargeable battery.
- 80-hour approximate operating time or one month with the typical non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function.
- Low battery warning.
- Equipped with 230Vac 50 Hz battery charger.
- Bi-directional RS232/C port for connection to printer.
- Bi-directional RS232/C port for PC, radio modem, or portable terminal.
- IR input for managing the remote control.
- **Fitted with thermal printer in the TPWLKIP and TPWLKIPM versions.**

MAIN FUNCTIONS

- The user can select the operating modes directly using the dedicated key*:
 - High resolution display x 10
 - Precision weighing with temporary recalibration via a sample weight (for internal factory use)
 - Net/Gross
 - Lb to Kg converter
 - Free conversion factor (for meter and litre counters etc.)
 - Weight totalizer
 - Formulizer
 - +/- controller with quick target and threshold input
 - Percentage weighing
 - Percentage batching with programmable target
 - Piece counter
 - Hold
 - Alibi memory (optional)
- Access to the user menu is gained using the dedicated key* to adjust the weighing filter, date and time, setpoint and tare weight, which the user can access by entering a programmable access password.

** These quick access keys to the menus can be blocked by configuring a dedicated password.*

AVAILABLE UPON PRICE ESTIMATE

- Special capacity e/o divisions.
- High resolution.