

## TPWP "PROFESSIONAL" SERIES PALLET TRUCK SCALE





- The user can select the operating modes directly using the dedicated key\*:
  - High resolution display x 10
  - Precision weighing with temporary recalibration via a sample weight (for internal factory use)
  - Net/Gross
  - Lb to Kg converter
  - Free conversion factor (for meter and litre counters etc.)
  - Weight totalizer
  - Formulizer
  - +/- controller with quick target and threshold input
  - Percentage weighing
  - Percentage batching with programmable target
  - Piece counter
  - Hold
  - Alibi memory (optional)
- Access to the user menu is gained using the dedicated key\* to adjust the weighing filter, date and time, setpoint and tare weight, which the user can access by entering a programmable access password.
  - \* These quick access keys to the menus can be blocked by configuring a dedicated password.

Pallet truck scale supplied with new DFW series integrated weighing indicator. The new program allows the user to easily access to main software functions and weighing operations. TPWA's flexibility makes them indispensable in harsh working enviroments for anyone who needs to weigh accurately any type of product on a pallet. Available also CE-M APPROVED.

## MAIN FEATURES

- Maximum lifting capacity: 2500 kg.
- Accuracy: +/- 0.05% of the maximum capacity.
- Fork dimensions 1150 x 550 x 85 mm.
- · Weighs about 125 kg.
- Bearing structure in extra thick sheet steel and oven-fire painted interior construction.
- Standard fitted with +/-160° swivelling column head.
- Steering wheels and double loading rollers with a poliurethane coating.
- 4 stainless steel IP68 load cells.
- Indicator with easy to clean ABS waterproof IP65 case enclosure built to withstand humid and dusty environments; large LCD display with 25 mm high contrast digits, which are clearly visible even in poor lighting conditions; 17-key numerical/functional membrane waterproof keyboard.
- Calibration and Set-Up configurable from keyboard or from PC with DINITOOLS.
- Power supply through built-in extractable rechargeable battery.
- 60-hour approximate operating time or three months with the typical non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function.
- · Low Battery Warning.
- Equipped with 230Vac 50 Hz battery charger.
- Bi-directional RS232/C port configurable for connection to printer.
- Bi-directional RS232/C serial output for radio modem, PC or portable terminal.
- IR input for managing the remote control.

## AVAILABLE UPON PRICE ESTIMATE

- · Special steering wheels.
- 680 mm fork width.
- Special fork length from 850 to 1500 mm.
- · Special capacity e/o divisions.
- · High resolution.