



## TECHNICAL SPECIFICATIONS

| Physical Specifications     |                                    |
|-----------------------------|------------------------------------|
| Length                      | 2,695mm                            |
| Width                       | 2,695mm                            |
| Height                      | 610mm                              |
| Construction                | Steel and Aluminum                 |
| Performance Specifications  |                                    |
| Length                      | 2,440mm                            |
| Width                       | 2,440mm                            |
| Height                      | 2,440mm                            |
| Measurement Increment       | L25mm W25mm H12.5mm                |
| Minimum                     | L460mm x W460mm x H460mm           |
| Protrusion Capture          | L75mm x W75mm x H50 mm             |
| Lighting Conditions         | Indoor lighting                    |
| Data Capture                | Time @ 2-4 seconds                 |
| Technical Specifications    |                                    |
| Dimensioning Devices        | 4 Infrared 3D Cameras              |
| Connectivity                | WIFI (Ethernet Available)          |
| Data Output                 | IP Telegram (ASCII) (Customizable) |
| Image Output                | JPEG                               |
| User Interface              | Built Into Weight Scale GUI        |
| Power Requirements          | 230 VAC                            |
| Operating Temperature       | -10°C to +40°C                     |
| Humidity                    | Up To 90%, Non-Condensing          |
| Certifications              | NTEP Cert #17-037P                 |
| Photographic Camera         | 1 Camera                           |
| Administrative Access       | Remote Access                      |
| Installation Specifications |                                    |
| Ceiling Mounted             | Rigid (typical)                    |
| Ceiling Height              | 355mm                              |
| Sensor Height               | 305mm                              |
| Open Floor Space            | 250mm x 250mm                      |
| Measurement Area            | 200mm x 200mm                      |
| Calibration Guided          | 2 Minute Calibration               |
| Warranty and Support        |                                    |
| Warranty                    | 1 Year                             |



CUBIX By Positive Weighing Solutions Ltd  
The sole distributor for the  
CUBIX Dimensioning System outside of the US.  
Get in touch now to discuss what you need  
and get a quote.

**POSITIVE**  
WEIGHING SOLUTIONS

Unit 8 The Clifton Centre, Spring Lane South,  
Malvern, WR14 1BJ



Call: **01684 561 002** Email: **info@positiveweighing.co.uk**