

TPWET "ENTERPRISE TOUCH SCREEN" SERIES PALLET TRUCK SCALE



Pallet truck fitted with digital weight indicator and advanced data management. Suitable for applications such as formulation, piece counting, totalisation, memorisation of stock movements, bar code reading, printouts, etc. The wide range of available interfaces and software applications make this instrument truly be a mobile weighing station integrated to a company's computer system.

Available also CE-M APPROVED.

MAIN FEATURES

- Maximum lifting capacity: 2000 kg.
- Accuracy: +/- 0.1% of the maximum capacity in the versions for internal use.
- Accuracy: +/- 0.05% of the maximum capacity in the "M" approved versions.
- Fork dimensions 1150 x 550 x 85 mm. Weighs about 125 kg.
- Bearing structure in extra thick sheet steel and oven-fire painted interior construction.
- **Standard fitted with +/-160° swivelling column head.**
- Steering wheels and double loading rollers with a poliurethane coating.
- 4 stainless steel IP68 shear-beam load cells.
- Weighing indicator **with colour touch screen** with easy to clean ABS waterproof IP65 enclosure built to withstand humid and dusty environments.
- Slot for built-in micro SD for recording logos.
- Configuration, calibration and diagnostics from keyboard or PC with DINITOOLS.
- Power supply through built-in extractable rechargeable battery. Fitted with battery charge.
- The operating time is of about 10 hours of continuous use, or 24/24h with second optional rechargeable battery.
- Programmable auto power saving function. Battery level indication.
- Equipped with 230Vac 50 Hz battery charger.
- RS232/C port for connection to printer, radio module, remote scale.
- RS232/C port on RJ connector for connection to PC.
- **Fitted with time/date and Alibi Memory.**
- **Fitted with thermal printer** with RS232/C dedicated bidirectional port (TPW20ETP and TPW20ETPM version)

Available upon request

- Special steering wheels.
- 680 mm fork width.
- Special fork length from 850 to 1500 mm.
- Special capacity e/o divisions.
- High resolution


BASIC FUNCTIONS

- Standard version with "AF01" software for advanced totalisation, in loading/unloading, formulation; functioning as PC terminal (data entry protocol communication); database of 1000 articles; 200 customers/suppliers, 300 tares, 4 independent
- Viewable and printable total levels, bar code reading with article activation; 15 configurable and printable text IDs (i.e.: Code, lot ID, Operator ID, shift number, etc.), A.C.W. (Automatic Calibration Warning): automatically advises to check the configurable calibration. Customisable printouts.
- Thanks to the programmable Touch Screen Display, you can create custom-made interfaces for any application

OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- **Extractable** rechargeable battery power supply.
- Virtual printer integrated with Memory Card.
- Thermal and Virtual printer integrated with Memory Card.
- Radio transmission / WI-FI / Bluetooth.
- Control light.
- Parking brake.
- Special versions by price estimate: 680mm fork width; special fork length from 850 to 1500mm; 3000kg capacity, high resolution.
- Special steering wheels.

POSITIVE WEIGHING SOLUTIONS ARE ABLE TO OFFER CUSTOM DEVELOPMENT OF PROGRAMS FOR SPECIFIC PROCESS REQUIREMENTS

Available versions			
Code	Max (kg)	d (kg)	CE-M 3000e (kg)
TPW20ETP	500 / 1000 / 2000	0.2 / 0.5 / 1	
TPW20ETPM 	1000 / 2000		0.5 / 1

Note : The capacity and divisions are relative, i.e. on model ref TPW20ETP, up to 500kg, the divisions are 0.2kg, up to 1000kg the divisions are 0.5kg and up to 2000kg the divisions are 1kg.

