



More information on the website  
[radwag.com/en/info,w1,YZ5](https://radwag.com/en/info,w1,YZ5)

# PUE 7.1.32.HRP High Resolution Scale

WP-350-0002



The drawings, photos and graphics used are for illustrative purposes only.

## Datasheet

| Metrological parameters        |                                   |
|--------------------------------|-----------------------------------|
| Maximum capacity [Max]         | 32 kg                             |
| Minimum load                   | 5 g                               |
| Preload range                  | 4 kg                              |
| Readability [d]                | 0.1 g                             |
| Tare range                     | -32 kg                            |
| Repeatability                  | 0.1 g                             |
| Linearity                      | ±0.3 g                            |
| Stabilization time             | 2 s                               |
| Adjustment                     | internal (automatic)              |
| Physical parameters            |                                   |
| Display                        | 5.7" resistive colour touchscreen |
| Weighing pan dimensions        | 360×280 mm                        |
| Device dimensions W x D x H    | 360×313×170 mm                    |
| Packaging dimensions W x D x H | 560×473×360 mm                    |
| Net weight                     | 24.7 kg                           |

| Physical parameters      |                                                           |
|--------------------------|-----------------------------------------------------------|
| Gross weight             | 28.7 kg                                                   |
| Construction             |                                                           |
| Protection class         | IP 66 / 67 construction, IP 43 terminal                   |
| Construction             | aluminum                                                  |
| Weighing pan material    | Stainless steel AISI304                                   |
| Communication interface  |                                                           |
| Communication interface  | 2×RS232, 2×USB-A, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi |
| Electrical parameters    |                                                           |
| Power supply             | 100 – 240 V AC 50/60 Hz                                   |
| Environmental conditions |                                                           |
| Operating temperature    | +10 – +40 °C                                              |
| Relative humidity        | 15% – 80%                                                 |

**Repeatability** is expressed as the standard deviation of ten load placements.

**Relative humidity** under non-condensing conditions.

**Stabilization time** under optimal environmental conditions.

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



## Accessories (Additional Fee)

Displays

Transponder card readers

RS 232 cables (scale - Ethernet)

RS 232 cables (scale - printer)

Antivibration Tables

Barcode scanners

Label Printers

Receipt Printer

Additional Weighing platforms Module

RS 232 – USB Converter

## Software (Additional Fee)

• E2R Weighing [WX-010-0099]

• Label Editor R02 [WX-010-0094]

• R-Lab [WX-010-0080]

• RADWAG Development Studio [WX-010-0104]

• RAD Key [WX-010-0005]

• RADWAG Remote Desktop [WX-010-0107]

• Scale Editor 2.1 [WX-010-0173]

Device dimensions W x D x H

